



#### Drawers colours



### ALV600500 - PROCEDURE TROLLEY COD. 6080/v

#### BODY

Structure made of powder-coated steel RAL 9006, thickness 10/10, finished with acrylic polyurethane enamels resistant to scratches, stains and corrosion.

Back of the trolley is made in technopolymer.

The structure can be washed and disinfected.

#### WORKTOP

Worktop made of self-extinguishing ABS mm with raised edges on three sides. It is resistant to scratches and stains and can be cleaned, washed and disinfected.

#### DRAWER UNIT

Drawers are made of powder-coated steel and run on telescopic soft-closing slides allowing their complete extraction. They are provided with built-in ergonomic ABS handles, stopper and spring lock to prevent them from opening while moving the trolley. Centralized key lock.

#### Standard drawer configuration:

1 drawer, ext. height 100 mm;

2 drawers, ext. height 150 mm

2 drawers, ext. height 200 mm

#### LEFT SIDE

Technopolymer pull-out worktop with stopper.

#### RIGHT SIDE

Ergonomic and anti-trauma aluminium push handle with plastic end caps.

#### BASE

Double shock absorbent bumper to prevent the trolley from turning over.

4 thermoformed swivel castors, Ø 125 mm, mounted on bearings; 2 are lockable.

\*Accessories for this trolley are available upon request.\*

Dim.800x640x1100 h mm

#### Position 1

Rev. 01 del 28/12/2022

TECHNICAL SHEETS - NR. / -

