ALFA 23/V - PROCEDURE TROLLEY COD. 6013

BODY

Structure made of powder-coated steel RAL 7035, thickness 10/10, finished with acrylic polyurethane enamels resistant to scratches, stains and corrosion. The structure can be washed and disinfected.

WORKTOP

Worktop made of self-extinguishing ABS, dimensions 760x400x60 h mm with raised edges on three sides. The worktop is resistant to scratches and stains and can be cleaned, washed and disinfected.

DRAWER UNIT

Drawers are made of powder-coated steel and run on soft-closing telescopic slides allowing their complete extraction. Drawers are provided with ergonomic and anti-trauma aluminium handles and stopper. Centralized key lock.

Standard drawer configuration:

- 1 drawer, height 100 mm;
- 2 drawers, height 150 mm;
- 2 drawers, height 200 mm;
- 2 open compartments, height 390 mm.

LEFT AND RIGHT SIDE

Ergonomic and anti-trauma aluminium push handle with plastic end caps.


BASE

Double perimetral and shock absorbent bumper to prevent the trolley from turning over. 4 thermoformed swivel castors, Ø 150 mm, mounted on bearings; 2 are lockable.

Accessories for this trolley are available upon request.

Dim.960x600x1110 h mm

Position 1





Rev. 01 del 28/12/2022

TECHNICAL SHEETS - NR. / -