

Drawers colours



Rev. 01 del 28/12/2022

TECHNICAL SHEETS - NR. / -

STORM - PROCEDURE TROLLEY COD. 7015

BEARING FRAME

Made by 4 powder-coated steel uprights that assure stability and consistency.

SIDE AND REAR PANELS

Made of technopolymer with rounded edges. They are designed for the positioning of accessories.

Load capacity: 100 kg

WORKTOP

Moulded technopolymer worktop, dimensions 700x500 mm, with raised edges on three sides.

DRAWER UNIT

Drawers are made of powder-coated steel and run on soft-closing telescopic slides allowing their complete extraction. They are provided with ergonomic and anti-trauma aluminium handles and stopper. Centralized key lock.

Standard drawer configuration:

- 2 drawers, height 100 mm;
- 2 drawers, height 150 mm;
- 1 drawer, height 250 mm

LEFT SIDE

Ergonomic and anti-trauma aluminium push handle with plastic end caps.

RIGHT SIDE

Technopolymer pull-out worktop.

BASE

- 4 PVC scratch-proof corner bumpers.
- 4 thermoformed swivel castors, Ø 125 mm, mounted on bearings; 2 are lockable.
- *Accessories for this trolley are available upon request.*

Dim.750x550x1060 h mm

Position 1

