



Drawers colours



ALV600730 - PROCEDURE TROLLEY COD. 6091/v

BODY

Structure made of powder-coated steel RAL 9006, thickness 10/10, finished with acrylic polyurethane enamels resistant to scratches, stains and corrosion.

Back of the trolley is made in technopolymer.

The structure can be washed and disinfected.

WORKTOP

Worktop made of self-extinguishing ABS mm with raised edges on three sides. The worktop is resistant to scratches and stains and can be cleaned, washed and disinfected.

DRAWER UNIT

Drawers are made of powder-coated steel and run on telescopic soft-closing slides allowing their complete extraction. They are provided with built-in ergonomic ABS handles, stopper and spring lock to prevent them from opening while moving the trolley. Centralized key lock.

Standard drawer configuration:

- 6 drawers, ext. height 200 mm
- 1 large drawer, ext. height 200 mm

LEFT SIDE

Technopolymer pull-out worktop with stopper.

RIGHT SIDE

Ergonomic and anti-trauma aluminium push handle with plastic end caps.

BASE

Double shock absorbent bumper to prevent the trolley from turning over.

4 thermoformed swivel castors, Ø 125 mm, mounted on bearings; 2 are lockable.

Accessories for this trolley are available upon request.

Dim.800x640x1100 h mm

Position 1

Rev. 01 del 28/12/2022

TECHNICAL SHEETS - NR. / -

